

PRODUCT NAME

St Marys Type S Masonry Cement

MANUFACTURER

St Marys Cement
55 Industrial Street
Toronto, ON M4G 3W9
Phone: 416-696-4411
Fax: 416-696-4435
www.stmaryscement.com

PRODUCT DESCRIPTION

St Marys Type S Masonry Cement is a special formulation of St Marys hydraulic cement produced specifically for use in mortar and in unit masonry construction.

BASIC USE

St Marys Type S Masonry Cement is recommended for use where higher mortar strength, such as for parging, load-bearing walls, foundation walls below grade, and walls designed with reinforcement, is required.

St. Marys Type S Masonry Cement is packaged in 33.3 kg (1 cubic foot) bags to enable the mason contractor to accurately proportion mortar on-site to conform to CSA A179.

**TECHNICAL DATA****APPLICABLE STANDARDS**

- CSA A3002 – Masonry and Mortar Cement Mortars proportioned according to CSA A179 will meet the requirements of that standard.

PRECAUTIONS

Avoid contact with eyes. Contains Portland Cement, which when mixed with water forms a calcium hydroxide solution. If splashed in eyes or skin, flush thoroughly with water. Avoid contact with skin, including contact with saturated clothing. Persistent discomfort requires prompt medical attention. For more information, reference the applicable Safety Data Sheet (SDS). The SDS should be consulted prior to use of this product and is available upon request or online at www.stmaryscement.com

AVAILABILITY

St Marys Type S Masonry Cement is available in bulk or in packaged form. Contact manufacturer for information on distribution and availability.

WARRANTY

Manufacturer will provide mill test certification that product meets and exceeds applicable CSA specifications.

St Marys Cement will not guarantee finish work, having no control over the use of this product.

TECHNICAL SERVICES

For technical assistance contact the local St Marys Cement office.